

Heavy Series (H)						
Specified outside diameter	Nominal Bore	Painted or uncoated pipe			Mass of galvanized pipe	
		Wall Thickness	Mass per unit length		Mass per unit length	
			P/E or T/O	T/C	P/E or T/O	T/C
mm	mm	(mm)	kg/m	kg/m	kg/m	kg/m
21.3	15	3.2	1.44	1.45	1.49	1.50
26.9	20	3.2	1.87	1.88	1.93	1.94
33.7	25	4.0	2.93	2.95	3.01	3.03
42.4	32	4.0	3.79	3.82	3.89	3.92
48.3	40	4.0	4.37	4.41	4.49	4.53
60.3	50	4.5	6.19	6.26	6.34	6.41
76.1	65	4.5	7.93	8.05	8.12	8.24
88.9	80	5.0	10.3	10.5	10.5	10.7
114	100	5.4	14.5	14.8	14.8	15.1
139.7	125	5.4	17.9	18.4	18.3	18.8
165.1	150	5.4	21.3	21.9	21.7	22.3

Medium Series (M)						
Specified outside diameter	Nominal Bore	Painted or uncoated pipe			Mass of galvanized pipe	
		Wall Thickness	Mass per unit length		Mass per unit length	
			P/E or T/O	T/C	P/E or T/O	T/C
mm	mm	(mm)	kg/m	kg/m	kg/m	kg/m
21.3	15	2.6	1.21	1.22	1.26	1.27
26.9	20	2.6	1.56	1.57	1.63	1.64
33.7	25	3.2	2.41	2.43	2.49	2.51
42.4	32	3.2	3.1	3.13	3.21	3.24
48.3	40	3.2	3.56	3.60	3.68	3.72
60.3	50	3.6	5.03	5.10	5.18	5.25
76.1	65	3.6	6.42	6.54	6.62	6.74
88.9	80	4.0	8.36	8.53	8.59	8.76
114	100	4.5	12.2	12.5	12.5	12.8
139.7	125	5.0	16.6	17.1	17.0	17.5
165.1	150	5.0	19.8	20.4	20.2	20.8

P/E Plain end
 T/O Threaded only
 T/C Threaded and coupled

Notes:

- 1 Pipes supplied square cut or bevelled. Bevelled from 32NB to 150NB
- 2 Pipes galvanized to EN/10240 or ISO 1461 whichever applicable

Light Series (L)						
Specified outside diameter	Nominal Bore	Painted or uncoated pipe			Mass of galvanized pipe	
		Wall Thickness	Mass per unit length		Mass per unit length	
			P/E or T/O	T/C	P/E or T/O	T/C
mm	mm	(mm)	kg/m	kg/m	kg/m	kg/m
21.3	15	2.3	1.08	1.09	1.13	1.14
26.9	20	2.3	1.40	1.41	1.47	1.48
33.7	25	2.9	2.20	2.22	2.28	2.30
42.4	32	2.9	2.82	2.85	2.93	2.96
48.3	40	2.9	3.25	3.29	3.37	3.41
60.3	50	3.2	4.51	4.58	4.66	4.73
76.1	65	3.2	5.75	5.87	5.95	6.07
88.9	80	3.3	6.76	6.93	6.99	7.16
114.3	100	3.6	9.83	10.1	10.1	10.4
139.7	125	4.5	15.0	15.5	15.4	15.9
165.1	150	4.5	17.8	18.4	18.2	18.8

Light Series (L1)						
Specified outside diameter	Nominal Bore	Painted or uncoated pipe			Mass of galvanized pipe	
		Wall Thickness	Mass per unit length		Mass per unit length	
			P/E or T/O	T/C	P/E or T/O	T/C
mm	mm	(mm)	kg/m	kg/m	kg/m	kg/m
21.3	15	2.3	1.08	1.09	1.13	1.14
26.9	20	2.3	1.39	1.40	1.46	1.47
33.7	25	2.9	2.20	2.22	2.28	2.30
42.4	32	2.9	2.82	2.85	2.93	2.96
48.3	40	2.9	3.24	3.25	3.36	3.40
60.3	50	3.2	4.49	4.56	4.64	4.71
76.1	65	3.2	5.73	5.85	5.93	6.05
88.9	80	3.6	7.55	7.72	7.78	7.95
114.3	100	4.0	10.8	11.1	11.1	11.4

Light Series (L2)						
Specified outside diameter	Nominal Bore	Painted or uncoated pipe			Mass of galvanized pipe	
		Wall Thickness	Mass per unit length		Mass per unit length	
			P/E or T/O	T/C	P/E or T/O	T/C
mm	mm	(mm)	kg/m	kg/m	kg/m	kg/m
21.3	15	2.0	0.947	0.958	1.00	1.01
26.9	20	2.3	1.38	1.39	1.45	1.46
33.7	25	2.6	1.98	2.00	2.06	2.08
42.4	32	2.6	2.54	2.57	2.65	2.68
48.3	40	2.9	3.23	3.27	3.35	3.39
60.3	50	2.9	4.08	4.15	4.23	4.30
76.1	65	3.2	5.71	5.83	5.91	6.03
88.9	80	3.2	6.72	6.89	6.95	7.12
114.3	100	3.6	9.75	10.0	10.0	10.3

P/E Plain end
 T/O Threaded only
 T/C Threaded and coupled

- Notes:
 1 Pipes supplied square cut or bevelled. Bevelled from 32NB to 150NB
 2 Pipes can be supplied galvanized to EN 10240 or ISO 1461, whichever applicable